

ALSTOM

KVA **1000** OA **65** °C RISE

HV **4800 x 13800 DELTA** BIL **95** KV

LV **480Y/277** BIL **30** KV

3 PHASE **60** Hz TRANSFORMER, **5.89** % IZ AT BASE KVA RATING

AL HV **AL** LV COND. ELEMENT **2815** LBS. TOTAL WEIGHT **7500** LBS.

280 GAL **OIL** AT **2069** LBS. LEVEL CHANGES **.31** INCH PER. 10°C.

FLUID LEVEL **10.5** INCHES FROM TOP OF HAND HOLE AT 25°C.

MAX TANK PRESS. POS **10.0** NEG **8.0** PSI

SERIAL # **PIG-0525**

DATE OF MFG: **07/03**

INSTRUCTION REFERENCE MANUAL IB9.210

TAPS	A	B	C	D	E		
13800 VOLTS	14400	13800	13200	12470	12000		
4800 VOLTS	4800						

TAPCHANGER MUST BE IN 'A' POSITION FOR 4800 VOLT OPERATION



NON-PCB
10487991-18799

300 WEST ANTELOPE ROAD, MEDFORD OREGON 97503-1089 USA



UNIT 5



ALSTOM





UNIT 5







UNIT 5





TAP CHANGER
MUST BE IN
POSITION "H"
FOR 4800 VOLTS

CAUTION
TAP CHANGER MUST BE ON
POSITION "H" FOR 4800 VOLTS

13800

4800

1

H2

3





X1 (BLACK) X2 (RED) X3 (WHITE) ↓ CW

TO VENT
PULL RING

X1



X3

240/480 ✓
RED X2
BLK X3
G
CCW

WAGO - CONFORMS TO
RELEVANT LEVEL OF THE
PROTECTIVE LEVEL
FOR THE PROTECTIVE LEVEL
FOR THE PROTECTIVE LEVEL
FOR THE PROTECTIVE LEVEL